



深圳市利路通科技实业有限公司

SHENZHEN LILUTONG TECHNOLOGY INDUSTRY CO., LTD.

NO. 83, PINGXIN NORTH RD., PINGHU, SHENZHEN 518111, CHINA

Tel: (86) 755 89636160 Fax: (86) 755 84692111 Email: huang@lltcable.com



CABLE SPECIFICATION 2c x 1.5 + E

<div style="display: flex; justify-content: space-around; align-items: flex-start;"> <div style="text-align: left;"> <p>Wires: Brown, blue (silicon E12)</p> <p>Wrapping: Mica tape</p> <p>Outer jacket: Red (LSZH LTS3)</p> </div> <div style="text-align: center;"> <p>Conductor: 1/1.35BC Earth wire: 1/0.8TC Wrapping: Fire resistant AL foil</p> </div> </div>		
Conductors	Material / purity	Bare Copper
	No./diameter of wire(s)	1
	Diameter	1.35
	Maximum resistance	12.1Ω/KM
Insulation	Type	Silicon - EI2
	Radial Thickness	0.6mm
	Colours/No.s	Brown,Blue
Binding Tape (1)	Type	Mica tape
	Earth/Drain Wire	0.8mm Tinned Copper
Binding Tape (2)	Type	AL tape
Sheathing	Type	low smoke halogen free - LTS3
	Radial thickness	0.7mm
	Diameter (min/max/nom)	7.2±0.2mm
	Colour	Red
	Marking (tag/reel)	100m/reel,500m/reel
Standards		BS 7629-1:2008 BS 6387:2013 (Category CWZ) EN 50200:2006 (Class PH30) EN 50200:2006 Annex E (30 mins) BS 5839-1:2013 (Clause 26.2d Standard)